



Product data sheet

Product category	Paraffin laser heaters
Brand	Qlima
Model	SRE 3430 C-2
Colour	White
EAN code	8713508773421

Technical specifications

Burner type	Electronic Injection Burner System (BI)	
Capacity (min./max.)	kW	1,08 / 3,00
For rooms up to	m ²	20 - 48
	m ³	48 - 120
Consumption (max.)	l/h	0,313
	g/h	250
Capacity tank	l	5
Autonomy (min./max.)	h	16 - 44
Power supply	V/Hz/Ph	220 - 240~ / 50 / 1
Power consumption at start	W	335
Power consumption	W	78 - 123
Sound pressure level	dB(A)	28 - 35
Dimensions (w x d x h)	mm	371 x 299 x 429
Net. weight	kg	8
Warranty	year	4

Safety features

Tip-over switch - Safety stop - Overheat protection - Safe top - CO₂ sensor - Child lock

All data is measured in accordance with applicable EU specified standards at the time of production. To be used for indicative purposes only.

Package content


Paraffin laser heater, Syphon pump, Transport cap, User manual

Accessories (to order)


Description	EAN code



guarantee



20 ft = 360
40 ft = 744
40 HQ = 930



W x D x H =
42 x 35 x 49 cm



Gross weight
9.5 kg

Qlima

Built-in CO₂ sensor

Tip-over safety switch



Daytimer



Energy saving mode



Advanced control system



Frost protection



Child lock



Adjustable thermostat



Safety stop

**MADE IN
JAPAN**

Made in Japan

CO₂ sensor: The user is informed when additional ventilation is required. The heater will be switched off when the room is not ventilated sufficiently.

Fuzzy logic: This heater is equipped with a self-regulating temperature control system. The heating mode can be set according to the requirements.

Semi-automatic operation: This heater is equipped with a 24-hour programmable timer and integrated thermostatic control to maintain the desired room temperature.

Wickless design: Provides clean and economical heating without wick maintenance or replacement.

Information display: The digital displays help to keep track of all the important heater functions.

Safety features: This heater is equipped with a combustion quality sensor, an over-heat protector, a tip-over switch, a safe top and a burner thermistor for safe heating.

Safety system: This heater is fitted with a safety system that automatically switches off the heater after approximately 36 hours of continuous operation.

Childproof lock: When this button is pressed, the operation of buttons will be blocked, except the on/off button.

Easy touch cap: A new way to easily mount the removable fuel tank cap without touching the tank directly.

Automatic airflow control: The speed of the built-in fan is self-regulatory, depending on the burning mode of the heater.

Automatic extension operation mode: When the fuel tank is almost empty, the display will show that the tank has to be refilled. The extension operation mode is activated and the heater switches to the lowest burning mode for more than one hour.

Made in Japan: This heater has been produced according to the ISO 9000:2015 Quality Control Standard.

Quiet operation: When heating the room, the device produces only a limited amount of sound. Also in the start up phase, the heater produces very little sound.
