

# Technical sheet Eurostove 65 S-Line

## Technical specifications

|                                                      |                     |                     |
|------------------------------------------------------|---------------------|---------------------|
| Article type                                         | Pellet stove        |                     |
| Brand                                                | Eurostove           |                     |
| Model                                                | Eurostove 65 S-Line |                     |
| Colour                                               | Red                 |                     |
| EAN code                                             | 8713508780047       |                     |
| Heating input - nominal                              | kW                  | 8,24                |
| Efficiency (nom. / reduced)                          | %                   | 91 / 92,7           |
| Autonomy (min./max.)                                 | h                   | 8 - 22              |
| EEI / Energy efficiency class                        | %                   | 128 / A+            |
| Consumption pellets (min./max.)                      | kg/h                | 0,6 - 1,7           |
| Warranty                                             | years               | 2                   |
| Power consumption                                    | W                   | 100                 |
| For rooms up to                                      | m³                  | 80 - 200            |
| Control                                              | Electronic          |                     |
| Power supply                                         | V/Hz/Ph             | 220 - 240~ / 50 / 1 |
| Hopper capacity                                      | kg                  | 13                  |
| Sound pressure level 1m                              | dB(A)               | 39 - 52             |
| Exhaust location                                     | back                |                     |
| Diameter exhaust                                     | mm                  | 80                  |
| Flue gas temperature (nom. / reduced)                | °C                  | 128 / 77            |
| Can be used in combined flue system                  | -                   |                     |
| Fuel compatibility                                   | 6x30mm pellet       |                     |
| Emission CO at 13% O <sub>2</sub> (nom. / reduced)   | mg/m³               | 125 - 500           |
| Emission OGC at 13% O <sub>2</sub> (nominal/reduced) | mg/m³               | 6,6 - 17            |
| Emission NOx at 13% O <sub>2</sub> (nominal/reduced) | mg/m³               | 126,6 - 135,6       |
| Material                                             | Metal               |                     |
| Dimensions (w x d x h)                               | mm                  | 470 x 476 x 899     |
| Dimensions package (w x d x h)                       | mm                  | 476 x 470 x 899     |
| Weight - unit                                        | kg                  | 81                  |
| Gross weight                                         | kg                  | 90                  |



All data is measured in accordance with applicable EU specified standards at the time of production. To be used for indicative purposes only.